

# MICHELIN<sup>®</sup> X MINE<sup>®</sup> D2

GET ALL THE BENEFITS OF MICHELIN<sup>®</sup>  
RADIAL TIRE TECHNOLOGY!

**With the MICHELIN<sup>®</sup> X MINE<sup>®</sup> D2 tire, you will get:**

- Excellent productivity and uptime
- Long tire life
- Maximum operator comfort and machine protection
- No chains or foam/poly fill required



# MICHELIN® X MINE® D2

This rugged MICHELIN® super L5 traction radial designed to give maximum protection in severe hard rock quarries, underground mines, scrap and solid waste applications.

## THE BENEFITS OF MICHELIN® RADIAL TIRES

### Exceptional Performance:

- Excellent traction and flotation; outstanding stability; enhanced operator comfort; less vehicle damage

### Excellent Productivity:

- Resistance to impacts and cuts means fewer flats

### Low Operating Costs:

- Long-lasting, even-wearing tread pattern; durable with low rolling resistance for efficient fuel economy; easy to repair

## THE TIRE OF CHOICE FOR:



LOADERS



UNDERGROUND HAULERS



UNDERGROUND LOADERS



### Increased Productivity

The ultra-deep L5 rock tread with massive buttressed shoulders and sidewalls provide resistance to damage in severe operating conditions.

### Maximum Comfort and Machine Protection

The MICHELIN® radial design helps protect valuable machine components while giving operators a smooth, comfortable ride. It eliminates the need for expensive foam/poly fill or chains.

### Long Tire Life

The combination of multiple steel belts, cut-resistant rubber compounds and a heavy-duty casing means fewer flats.

MICHELIN NORTH AMERICA, INC.

One Parkway South, P.O. Box 19001, Greenville, SC 29602-9001

1-877-574-8473

[www.michelinearthmover.com](http://www.michelinearthmover.com)

© 1999 MNA, Inc.  
MEL41597 (Rev 7/12)

SIZE	TREAD DEPTH	
	32nds	MM
7.50 R 15 TT	58	46
8.25 R 15 TT	61	48
10.00 R 15 TT	61	48
350/65 R 15 TL	45	36
400/80 R 15 TL	43	34
14.5 R 15 TL	61	48
9.00 R 20 TT	64	51
12.00 R 20 TT	72	57
14.00 R 20 TL	61	48
12.00 R 24 TL	72	57
15.5 R 25 TL	76	60
17.5 R 25 TL **	82	65
18.00 R 25 TL **	103	82
20.5 R 25 TL **	93	74
23.5 R 25 TL **	105	83
26.5 R 25 TL **	115	91
29.5 R 25 TL **	126	100
29.5 R 29 TL **	126	100
35/65 R 33 TL **	117	93
45/65 R 39 L5R TL **	146	116
45/65 R 45 L5R TL **	146	116
55/80 R 57 SR TL	150	119
55/80 R 57 HR TL	150	119
55/80 R 57 LC TL	150	119
60/80 R 57 SR TL	149	118
60/80 R 57 HR TL	149	118
50/65 R 51 HR TL **	146	116
50/65 R 51 SR TL **	146	116

